

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 August 2004 (19.08.2004)

PCT

(10) International Publication Number
WO 2004/070751 A3

(51) International Patent Classification⁷: **H02H 3/00**,
9/08, 3/16

(21) International Application Number:
PCT/US2004/002575

(22) International Filing Date: 30 January 2004 (30.01.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/444,469 3 February 2003 (03.02.2003) US
10/690,776 22 October 2003 (22.10.2003) US

(71) Applicant: **LEVITON MANUFACTURING CO., INC.**
[US/US]; 59-25 Little Neck Parkway, Little Neck, NY
11362 (US).

(72) Inventors: **GERMAIN, Frantz**; 142-10 243 Street,
Rosedale, NY 11422 (US). **RICHTER, James**; 75-15


210th Street, Bayside, NY 11364 (US). **HERZFELD, David**; 8 Woodhollow Lane, Huntington, NY 11743 (US). **CALIXTO, Armando**; 79-14 261 Street, Floral Park, NY 11004 (US). **CHAN, David**; 83-34 250th Street, Bellerose, NY 11426 (US). **STEWART, Stephen**; 4710-2 Hillcrest Drive, Berrien Springs, MI 49103 (US).

(74) Agents: **SUTTON, Paul, J. et al.**; Greenberg Traurig, LLP, 885 Third Avenue, New York, NY 10022 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: **CIRCUIT INTERRUPTING DEVICE AND SYSTEM UTILIZING BRIDGE CONTACT MECHANISM AND RESET LOCKOUT**



(57) Abstract: A GFCI device (10) which has reverse wiring protection is provided where no power is present at the face terminals (32, 34) even when the device is reversed wired. The device has a pair of movable bridges connected to its terminals. The terminal bridge pair makes contact with the load and the face terminals (32, 34) providing power to these terminals when the device is reset. The device also has a reset lockout feature that prevents it from being reset after having been tripped if the circuit interrupting portion of the device is non-operational.

WO 2004/070751 A3